

IS: 15683

 CM/L: 3985085



Fire Extinguisher



The quick & efficient flame knockdown property of CO2 gas makes it ideal for tackling fires involving inflammables liquids like petrol, oil, paints, solvents and industrial gases. It is also suitable for sophisticated machineries. CO2 extinguishes the fire within seconds by dilution of oxygen and chilling effect.

Note : Check 3D Hologram on Firestop Fire Extinguishers for Genuineness.

FEATURES

- Pure High Grade CO2 Gas
- Available in 2 capacities
- Stunning looks & design
- ISI Marked

PERFORMANCE DATA

MODEL	FEC2	FEC4
Capacity (In Kgs.)	2	4.5
Fire Rating	13B	34B
Average Discharge Time	10 sec	17 sec
Height (Approx.)	58.00 cm	70 cm
Diameter (Approx.)		
Gross Weight (Approx.)	8 Kgs	16 Kgs
Operating Temperature Range	-10°C TO +55°C	
Service Pressure	55 Bar	
Maximum Service Pressure	90 Bar	
Test Pressure	250 Bar	
Certification	BIS (ISI)	

SUITABLE FOR CLASSES OF FIRE



Firestop fire extinguishers are guaranteed against any manufacturing defects.
 Design & specification may be changed without notice in view of technical upgradation.



Firestop
 coz Life is Priceless

Log on to
www.firestopgroup.com

Email
contact@firestopgroup.com

Tel : Number
 +91 79-22161962

Tel Fax
 +91-79-22173963

Firestop Engineers

20, Amarnath Indl. Estate,
 Old Manek Chowk Mill Compound,
 Near Idgah Chowki,
 Ahmedabad-16 - Gujarat India