

IS: 15683



CM/L: 3985085

# Foam

Stored Pressure Fire Extinguisher



This extinguisher forms a thick layer of foam over the burning surface, effectively cutting of atmospheric supply of oxygen to the burning surface thereby smothering the fire and preventing re-ignition. Foam extinguishes fire by giving blanketing effect.

**Note :** Check 3D Hologram on Firestop Fire Extinguishers for Genuineness.

## FEATURES

- AFFF Agent to combat A & B Class Fires
- Stunning looks & Design
- High Quality Powder Coating
- Squeeze Valve for easy to use
- High Quality Nozzle for Effective fire fighting
- ISI Marked

## SUITABLE FOR CLASSES OF FIRE



## PERFORMANCE DATA

MODEL	FEF9
Capacity (In Ltrs.)	9
Fire Rating	4A & 34B
Average Discharge Time	28 sec
Height (Approx.)	60 cm
Diameter (Approx)	175 mm
Gross Weight (Approx.)	12.5 Kgs
Operating Temperature Range	+5°C TO +55°C
Service Pressure	15 Bar
Maximum Service Pressure	16 Bar
Test Pressure	35 Bar
Certification	BIS (ISI)

Firestop fire extinguishers are guaranteed against any manufacturing defects.  
Design & specification may be changed without notice in view of technical upgradation.



**Firestop**  
coz Life is Priceless

Log on to  
[www.firestopgroup.com](http://www.firestopgroup.com)

Email  
[contact@firestopgroup.com](mailto:contact@firestopgroup.com)

Tel : Number  
+91 79-22161962

Tel Fax  
+91-79-22173963

## Firestop Engineers

20, Amarnath Indl. Estate,  
Old Manek Chowk Mill Compound,  
Near Idgah Chowki,  
Ahmedabad-16 - Gujarat India